

## DECLARATION OF CONFORMITY

### **P Series – P6xxx, P4xxx, P8xxx, PLASTX Series – PLXx Partlow MIC14xx+, MIC16xx+, MIC18xx+**

This product is manufactured at the premises of West Control Solutions, The Hyde Business Park, Brighton, East Sussex, BN2 4JU, England, UK

This declaration of conformity is issued under the sole responsibility of the manufacturer.

The objects of this declaration are the products identified using the model numbers derived from the tables listed below.

The objects of this declaration are in conformity with the following European Union harmonisation legislation:

- 2014/30/EU Electromagnetic Compatibility
- 2014/35/EU Low Voltage Directive
- 2011/65/EU Restriction of Hazardous Substances in Electrical and Electronic Equipment and subsequent amendment 2015/863/EU

The assessment of conformity has been made using the standards route to compliance. The standards this product is compliant with are listed below: -

**EN 61326-1:2013 Electrical equipment for measurement, control and laboratory use — EMC Requirements — Part 1: General Requirements**

**FCC Title 47 Chapter 1A Part 15B RADIO FREQUENCY DEVICES  
FCC Title 47 Chapter 1A Part 18 INDUSTRIAL, SCIENTIFIC, AND MEDICAL EQUIPMENT  
EN55011:2009 + A1:2010 Industrial, scientific and medical equipment – Radio Frequency disturbance characteristics – Limits and methods of measurement**

This product has been evaluated as Class A equipment suitable for operation in Industrial Locations against this standard.

#### WARNING

This is a Class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.

**UL 61010-1 Edition 3, Safety requirements for electrical equipment for measurement, control and laboratory use; Part 1: General Requirements**

**BS EN IEC 63000:2018, Technical documentation for the assessment of electrical and electronic products with respect to the restriction of hazardous substances.**

This declaration is made for and on behalf of Fortive by Paul Barber, who has been designated as the responsible person for the purpose of the regulations.

Signature:

  
\_\_\_\_\_  
(Paul Barber)

Date of Issue:

11 January 2021  
\_\_\_\_\_

Model Number	P	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x
<b>Size</b>																
1/16th DIN (48 x 48 x 110)mm		6														
1/8th DIN (96 x 48 x 100)mm		8														
1/4th DIN (96 x 96x 100)mm		4														
<b>Function</b>																
Standard Indicator			0	1												
Standard Controller			1	0												
Valve Motor Drive (VMD) Controller			1	7												
Limiter (Requires OP1 Relay)			7	0			1									
<b>Branding</b>																
West					0											
West USA (Farenheit default)					1											
PartLow					2											
Dynapar (Requires 1/8th Din Indicator)		8	0	1	4											
Anderson (Requires 1/8th Din Controller)		8	1	0	5											
<b>Input type</b>																
3 Wire RTD or DC mV						1										
Thermocouple						2										
DC mA						3										
DC Voltage						4										
<b>Option Slot 1 *</b>																
Not fitted							0									
Relay Output							1									
DC Drive Output for SSR							2									
Linear 0-10V DC Output							3									
Linear 0-20mA DC Output							4									
Linear 0-5V DC Output							5									
Linear 2-10V DC Output							6									
Linear 4-20mA DC Output							7									
Triac Output							8									
<b>Option Slot 2 *</b>																
Not fitted								0								
Relay Output								1								
DC Drive Output for SSR								2								
Linear 0-10V DC Output								3								
Linear 0-20mA DC Output								4								
Linear 0-5V DC Output								5								
Linear 2-10V DC Output								6								





Model Number	PLX8	2	x	x	x	x	x	2	0	1	0	Sxxx
<b>Option Slot 1</b>												
Not Fitted			0									
Relay			1									
DC drive for SSR			2									
Triac			8									
<b>Option Slot 2</b>												
Not Fitted			0									
Relay			1									
DC drive for SSR			2									
Triac			8									
<b>Option 3</b>												
Not Fitted					0							
Relay					1							
DC drive for SSR					2							
<b>Option A</b>												
Not fitted					0							
RS485 comms					1							
<b>Power Supply</b>												
100-240VAC								0				
24-48VAC or DC								2				