DECLARATION OF CONFORMITY

West ProVU4 Series Controller PMA Pro96-1 Series Controller **CAL4600 Series Controller** West Pro-EC44 Series Controller (And corresponding branded products)

This product is manufactured at the premises of West Control Solutions, The Hyde Business Park, Brighton, East Sussex, BN2 4JU, England, UK

This declaration of conformity is issued under the sole responsibility of the manufacturer.

The objects of this declaration are the products identified using the model numbers derived from the tables listed below.

The objects of this declaration are in conformity with the following European Union harmonisation legislation:

2014/30/EU Electromagnetic Compatibility

2014/35/EU Low Voltage Directive

2011/65/EU Restriction of Hazardous Substances in Electrical and Electronic Equipment

The assessment of conformity has been made using the standards route to compliance. The standards this product is compliant with are listed below: -

EN 61326-1:2013 Electrical equipment for measurement, control and laboratory use — EMC Requirements — Part 1: General Requirements

FCC Title 47 Chapter 1A Part 15B RADIO FREQUENCY DEVICES FCC Title 47 Chapter 1A Part 18 INDUSTRIAL, SCIENTIFIC, AND MEDICAL EQUIPMENT EN55011:2009 + A1:2010 Industrial, scientific and medical equipment - Radio Frequency disturbance characteristics - Limits and methods of measurement

This product has been evaluated as Class A equipment suitable for operation in Industrial Locations against this standard.

WARNING

This is a Class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.

UL 61010-1 Edition 3, Safety requirements for electrical equipment for measurement, control and laboratory use; Part 1: General Requirements

EN50581:2012, Technical documentation for the assessment of electrical and electronic products with respect to the restriction of hazardous substances.

This declaration is made for and on behalf of Danaher by Stephan Sommer, who has been designated as the responsible person for the purpose of the regulations.

Signature: Step 2 Step 2 Date of Issue: 15/04/16

Page 1 of 5





Model Number (ProVU4):	V4	*	X	×	X	X	X	X	X	X	×	х	Х	×
Regional Default	1900	611		100	77	3.0	7, 4	ter i	74		027		100	11
West Non-US defaults	T	0	П					Т	T	T				
West USA defaults		1						t	1	1			\dashv	
PMA (Pro96-1)		3	1						+	+			\dashv	
CAL		6			Н			\vdash						_
Blank		В						H					\dashv	
No overlay		N										T	\dashv	
Omega		4						\vdash				T	\dashv	_
Unit Type	Salar Salar							1	341			100		Pil.
Grpahical Controller			С							П			Т	
Graphical Controller, Datalogger/RTC			D					ĺ					1	_
Graphical Controller with USB Port			U										T	
Controller /Recorder with USB Port			R		T								Ť	
Profiler	PARTICIPATION OF THE PARTICIPA						4		es Li		41			101
Not fitted				0									Ĩ	
Profiler				Р	T	Ì					T	T	Ť	
Power Supply	10 2 2 3 1		0				100	14	128	100				34
100-240V AC					0									
24-48V AC or DC					2									
Option Slot 1														
Not fitted						0					\Box		Т	
Relay Output						1								
DC Drive Output for SSR						2								
Linear DC Output						L								
Triac Output						8								
Option Slot 2		FAT.		746						M		1.11		
Not fitted							0							
Relay Output							1							
DC Drive Output for SSR							2							
Linear DC Output							L							
Triac Output							8							
Dual relay Output							9							
Dual SSR Driver Output							S							
24VDC Transmitter Power Supply							Т							
Option Slot 3		10				H				7			(1)	
Not fitted								0						
Relay Output								1						
DC Drive Output for SSR								2						
Linear DC Output								L						
Triac Output								8						





Dual relay Output				9						L
Dual SSR Driver Output				S						
24VDC Transmitter Power Supply				T						
Option Slot 4										
Not fitted					0					
4 Relay Output					1					
Option Slot A								To the		
Not fitted						0				
RS485 Serial Comms						1				
Digital Input						3				
Auxiliary Input A						4				
Ethernet Port						5				
Option Slot B					11-7			14		
Not fitted							0			
Auxiliary Input B							R			
Option Slot C										
Not fitted								0		
Reserved for future options								1		
Manual & HMI Language		W. 3"	-				A.	111		
English									1	
French									2	
German									3	
Italian									4	
Spanish									5	
Russian									R	
Packing Options		Mar.	HAL					IV.		
Single Pack with Concise Manual										0
Bulk Pack with 1 Concise Manual per unit - Minimum 20 pcs										1
Bulk Pack No Manual - Minimum 20 pcs										2
Bulk Pack with 1 Full Manual per unit - Minimum 20 pcs										3
Single Pack with 1 Full Manual per unit										5



Model Number	EC440	X	×	х	х	×	×	x	×	x	x	×	×	1
				112							1	10		
Unit Type		4.7				_	T	_	T	_	I			
Controller	14	С	_			_	1	1	-	\vdash	<u> </u>			L
Controller with USB Port		U		_	_	_	_	1	-					L
Controller/ Recorder		Х				_		1	1	_				
Controller /Recorder with USB Port		R												
Profiler								Щ			D.			
Not fitted			0											
Profiler			Р											
Power Supply							B							
100-240V AC				0										
24-48V AC or DC				2										
Control Loops	History													
One Control Loop					1									
One Loop + Auxiliary Input					Α									
Two Control Loops					2									
Base Option 1			Hi											
Relay Output						1								
Relay Output + Linear DC Output						М								
Base Option 2						1					Ni			
Not fitted							0							
Relay Output + Linear DC Output	ĺ						М							
Plug-in Module Slot 1	Milki													
Not fitted								0			П		\Box	
Relay Output	İ	i	T					1			Ì			
DC Drive Output for SSR								2						
Linear DC Output								L						
Triac Output								8						
Plug-in Module Slot 2														
Not fitted									0					
Relay Output									1					
DC Drive Output for SSR									2					
Triac Output									8					
Dual relay Output									9					
Dual SSR Driver Output									Υ					
24VDC Transmitter Power Supply									Т					
Plug-in Module Slot 3								M						
Ser Letter										0				



Relay Output	1	Ī	1	1
DC Drive Output for SSR	2	Ť	T	T
Triac Output	8			
Dual relay Output	9			
Dual SSR Driver Output	Υ			
24VDC Transmitter Power Supply	Т			
Plug-in Mod <u>ule</u> Slot A				
Not fitted	(
RS485 Serial Comms - Modbus RTU	1			Ì
Digital Input	3			
Auxiliary Input A	4			
Ethernet Port - Modbus TCP	5			
Option C				
Not fitted		0		
Multiple Digital Input		1		
Manual & HMI Language				
English			1	
French			2	
German			3	
Italian			4	
Spanish			5	



